Putoline
MOTORCYCLE OILS

Product Information PT.20.04
19-01-2024

TT Scooter

Description

TT Scooter is a synthetic, low smoke, clean-burning, high performance 2-stroke oil. The product has the following properties:

- Minimises smoke development
- Minimises carbon deposits
- Counteracts fouling on the spark plugs
- Extends the service life of the engine TT Scooter is recommended for regular and high performance road use. It is suitable for pre-mix and injection systems. Recommended mix ratio: 2-4%.

Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Specifications

API TC
JASO FD
ISO-L-EGD
TISI

Typicals

Density at 15 °C, kg/l	0,866
Viscosity 40 °C, mm²/s	38,70
Viscosity 100 °C, mm²/s	7,10
Viscosity Index	147
Flash Point COC, °C	122
Pour Point, °C	-45
Total Base Number, mgKOH/g	1,4

Available packagings

70471	74424	70476	70472
1 L bottle	20 L Bag in Box	60 L drum	200 L drum