

Product Information PW.30.03

19-01-2024

Putoline DOT 5.1 Brake Fluid

Description

DOT 5.1 Brake Fluid is a high-grade, synthetic brake fluid. The product exceeds the requirements of motorcycle manufacturers. Instructions for use:

- Replace the brake fluid every two years to continue to guarantee correct functioning
- Only use DOT 5.1 Brake Fluid when specified. Please consult your instruction book for the correct specifications
- Can be mixed with synthetic DOT 3 and DOT 4

Application

Putoline Oil is a high-quality supplier of a wide range of lubricants and maintenance products. We only supply products for motorised two-wheelers and that makes us unique! Our years of experience, combined with continuous research results in the best price/quality ratio. Manufacturing our own products guarantees a consistently high quality. Putoline Oil, Driven by Technology!

Please refer to the advisory database for use of the correct product.

Specifications

FMVSS 116 DOT 5.1

SAE J1703, ISO 4925

Typicals

Density at 15 °C, kg/l	1,070
Viscosity -40 °C, mm ² /s	776
Viscosity 100 °C, mm ² /s	2,30
Flash Point PM, °C	150
Boiling Point (reflux) , °C	275
Wet Boiling Point, °C	195
pH - 50% in ethanolsolution	8,5

Available packagings



74043

500 ml bottle



74287

20 L Bag in
Box